

Python For Data Science Cheat Sheet

NumPy Basics

Learn Python for Data Science Interactively at www.DataCamp.com



NumPy


The NumPy library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention:

```
>>> import numpy as np
```



NumPy Arrays



Creating Arrays

```
>>> a = np.array([1,2,3])
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]),
      dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4))
>>> np.ones((2,3,4),dtype=np.int16)
>>> d = np.arange(10,25,5)

>>> np.linspace(0,2,9)

>>> e = np.full((2,2),7)
>>> f = np.eye(2)
>>> np.random.random((2,2))
>>> np.empty((3,2))
```

Create an array of zeros
Create an array of ones
Create an array of evenly spaced values (step value)
Create an array of evenly spaced values (number of samples)
Create a constant array
Create a 2x2 identity matrix
Create an array with random values
Create an empty array

I/O

Saving & Loading On Disk

```
>>> np.save('my_array', a)
>>> np.savetxt('array.npz', a, b)
>>> np.load('my_array.npy')
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")
>>> np.genfromtxt("my_file.csv", delimiter=',')
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Data Types

```
>>> np.int64
Signed 64-bit integer types
>>> np.float32
Standard double-precision floating point
>>> np.complex
Complex numbers represented by 128 floats
>>> np.bool
Boolean type storing TRUE and FALSE values
>>> np.object
Python object type
>>> np.string_
Fixed-length string type
>>> np_unicode_
Fixed-length unicode type
```

Inspecting Your Array

```
>>> a.shape
Array dimensions
>>> len(a)
Length of array
>>> a.ndim
Number of array dimensions
>>> a.size
Number of array elements
>>> a.dtype
Data type of array elements
>>> a.dtype.name
Name of data type
>>> a.astype(int)
Convert an array to a different type
```

Asking For Help

```
>>> np.info(np.ndarray.dtype)
```

Array Mathematics

Arithmetic Operations

```
>>> g = a - b
array([[-0.5,  0. ,  0. ],
       [-3. , -3. , -3. ]])
>>> np.subtract(a,b)
>>> b + a
array([[ 2.5,  4. ,  6. ],
       [ 5. ,  7. ,  9. ]])
>>> np.add(b,a)
>>> a / b
array([[ 0.66666667,  1.        ,  1.        ],
       [ 0.25,  0.4,  0.5        ]])
>>> np.divide(a,b)
>>> a * b
array([[ 1.5,  4. ,  9. ],
       [ 4. , 10. , 18. ]])
>>> np.multiply(a,b)
>>> np.exp(b)
>>> np.sqrt(b)
>>> np.sin(a)
>>> np.cos(b)
>>> np.log(a)
>>> e.dot(f)
array([[ 7.,  7.],
       [ 7.,  7.]])
```

Subtraction

Subtraction

Addition

Addition

Division

Division

Multiplication

Multiplication

Exponentiation

Square root

Print sines of an array

Element-wise cosine

Element-wise natural logarithm

Dot product

Comparison

```
>>> a == b
array([[False,  True,  True],
       [False, False, False]], dtype=bool)
>>> a < 2
array([True, False, False], dtype=bool)
>>> np.array_equal(a, b)
```

Element-wise comparison

Element-wise comparison

Array-wise comparison

Aggregate Functions

```
>>> a.sum()
Array-wise sum
>>> a.min()
Array-wise minimum value
>>> b.max(axis=0)
Maximum value of an array row
>>> b.cumsum(axis=1)
Cumulative sum of the elements
>>> a.mean()
Mean
>>> b.median()
Median
>>> a.correlcoef()
Correlation coefficient
>>> np.std(b)
Standard deviation
```

Copying Arrays

```
>>> h = a.view()
Create a view of the array with the same data
>>> np.copy(a)
Create a copy of the array
>>> h = a.copy()
```

Sorting Arrays

```
>>> a.sort()
Sort an array
>>> c.sort(axis=0)
Sort the elements of an array's axis
```

Subsetting, Slicing, Indexing

Subsetting

```
>>> a[2]
1
>>> b[1,2]
1.5
>>> b[0,1,2]
6.0
```

1	2	3
1.5	2	3
4	5	6

Select the element at the 2nd index
Select the element at row 1 column 2 (equivalent to `b[1][2]`)

Slicing

```
>>> a[0:2]
array([1, 2])
>>> b[0:2,1]
array([ 2.,  5.])
>>> b[:1]
array([[1.5, 2., 3.]])
```

1	2	3
1.5	2	3
4	5	6

Select items at index 0 and 1
Select items at rows 0 and 1 in column 1
Select all items at row 0 (equivalent to `b[0:1, :]`)
Same as `[1, :, :]`

```
>>> c[1,:]
array([[ 3.,  2.,  1.],
       [ 4.,  5.,  6.]])
```

1	2	3
3	2	1
4	5	6

Reversed array `a`

```
>>> a[ ::-1]
array([3, 2, 1])
```

1	2	3
3	2	1
2	1	0

Select elements from `a` less than 2

```
>>> a[a<2]
array([1])
```

1	2	3
1	0	1
0	1	2

Select elements `(1,0),(0,1),(1,2)` and `(0,0)`

```
>>> b[[1, 0, 1, 0], [0, 1, 2, 0]]
array([ 4.,  2.,  6., 1.5])
```

1	0	1	0
1	0	1	2

Select a subset of the matrix's rows and columns

Array Manipulation

Transposing Array

```
>>> i = np.transpose(b)
>>> i.T
```

Permute array dimensions
Permute array dimensions

Changing Array Shape

```
>>> b.ravel()
>>> g.reshape(3,-2)
```

Flatten the array
Reshape, but don't change data

Adding/Removing Elements

```
>>> h.resize((2,6))
>>> np.append(h,g)
>>> np.insert(a, 1, 5)
>>> np.delete(a,[1])
```

Return a new array with shape `(2,6)`
Append items to an array
Insert items in an array
Delete items from an array

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)
array([ 1,  2,  3, 10, 15, 20])
>>> np.vstack((a,b))
array([[ 1.,  2.,  3.],
       [ 1.5,  2.,  3.],
       [ 4.,  5.,  6.]])
>>> np.r_[e,f]
>>> np.hstack((e,f))
array([[ 7.,  7.,  1.,  0.],
       [ 7.,  7.,  0.,  1.]])
>>> np.column_stack((a,d))
array([[ 1, 10],
       [ 2, 15],
       [ 3, 20]])
>>> np.c_[a,d]
```

Concatenate arrays
Stack arrays vertically (row-wise)
Stack arrays vertically (row-wise)
Stack arrays horizontally (column-wise)
Create stacked column-wise arrays
Create stacked column-wise arrays
Create stacked column-wise arrays

Splitting Arrays

```
>>> np.hsplit(x,3)
[array([1]),array([2]),array([3])]
>>> np.vsplit(c,2)
[array([[ 1.5,  2.,  3.],
       [ 4.,  5.,  6.]]),
 array([[ 3.,  2.,  1.],
       [ 4.,  5.,  6.]])]
```

Split the array horizontally at the 3rd index
Split the array vertically at the 2nd index

